Amendment to the Claims

Listing Of Claims

- 1. (currently amended): A stable, aqueous-aqueous emulsion comprising
 - (1) a dispersed aqueous phase comprising a molecule or combination of molecules meeting the following criteria:
 - (a) water stability solubility of greater than 5%; and
 - (b) MW >about 200 and < about 200,000; and
 - (2) a continuous phase comprising surfactant or surfactant system having micelles in rod-like shape,

wherein rod-like is defined by a surfactant parameter of surfactant or surfactants forming the micelle, Ns, of about 1/3 – 1/2, where Ns is defined by the equation:

 $Ns = V /la_o$

where

V = volume of the hydrophobic portion of the surfactant volume;

I = the length of the hydrocarbon claims of the surfactant; and

 a_o = effective area for head group[[.]];

wherein the molecules in the dispersed phase are selected from the group consisting of maltodextrins having MW of about 500 to 5000; PVP having MW of about 7000; dextran having MW of about 70,000; PEG having MW of about 1000, and mixtures thereof.

 (original): An emulsion according to claim 1, wherein molecule or combination of molecules in dispersed phase has solubility in water > 10%.

- (original): An emulsion according to claim 1, wherein molecule or combination of molecules in dispersed phase has solubility in water > 15%.
- (original): An emulsion according to claim 1, wherein molecule or combination of molecules in dispersed phase has MW > 250.
- (original): An emulsion according to claim 1, wherein molecule or combination of molecules in dispersed phase has MW < 195,000.
- (original): An emulsion according to claim 1, wherein surfactant system of continuous phase comprises alkali metal ether sulfate and cocoamidopropyl betaine.
- 7. (original): An emulsion according to claim 1, wherein the ratio of alkali metal ether sulfate to betaine is about 2:1.
- 8. (original): An emulsion according to claim 1, wherein the surfactant system of continuous phase comprises a surfactant blend comprising anionic and cocomonoethanolamide (CMEA) in combination with betaine.
- 9. (original): An emulsion according to claim 1, wherein the blend is used in ratio of alkali metal ether sulfate to betaine of about 4:1.

10.	(cancelled).
11	(cancelled).
12.	(cancelled).
13.	(cancelled).
14.	(original): An emulsion according to claim 1, additionally comprising sal
15.	(original): An emulsion according to claim 1, additionally comprising glycerin.

16. (currently amended): A process for forming a stable aqueous-aqueous emulsion which process comprises adding to surfactant or surfactant system having surfactant parameter of the surfactant or surfactants, Ns, of about 1/3 – 1/2, wherein Ns is defined by the equation:

 $Ns = V /la_0$

where

V = volume of the hydrophobic portion of the

surfactant volume;

I = the length of the hydrocarbon claims of

the surfactant; and

 a_0 = effective area for head group,

a molecule meeting the following criteria:

(a) water soluble_solubility of greater than 5%; and

(b) MW >about 200 and < about 200,000[[.]]; wherein said molecule is selected from the group consisting of maltodextrins having MW of about 500 to 5000; PVP having MW of about 7000; dextran having MW of about 70,000; PEG having MW of about 1000, and mixtures thereof.